

Product data sheet

HAVSO2S0022GSM

Characteristics

Variable speed drive, SOLAR, 2.2 kW 220V, 1 phase, HD, 1 phase motor



Main

Range of product	SOLAR
Product or component type	Variable speed drive
Product specific application	Solar pump
Network number of phases	1 phase
[Us] rated supply voltage	220 V AC - 15...15 % 150...440 V DC
Supply voltage type support	AC/DC
Supply frequency	50...60 Hz
Motor power kW	2.2 kW for heavy duty
Motor power hp	2.9 hp for heavy duty
Maximum transient current	21 A during 1 min (heavy duty) 25.2 A during 3 s (heavy duty) 28 A during 0 s (heavy duty)
Asynchronous motor control profile	Sensorless vector control (SVC) Voltage/frequency ratio (V/f)
Speed drive output frequency	0...400 Hz
Continuous output current	14 A

Complementary

Product destination	Asynchronous motors
Function available	MPPT function Auto start-run-stop Energy/flow calculator Pump cleaning Multi-speed operation Energy saving mode
Type of cooling	Fan
Regulation loop	Adjustable PID regulator
Acceleration and deceleration ramps	Linear adjustable separately from 0.01 to 6500 s
Frequency resolution	Analog input: 0.05/50 Hz
Analogue input number	1
Analogue input type	AI1 voltage: 0...10 V AI1 current: 0...20 mA
Discrete input number	4
Discrete input type	Programmable (DI1...DI4)
Analogue output number	1
Analogue output type	AO1 voltage/current: 0...20 mA or 0...10 V
Discrete output number	2

Discrete output type

configurable relay logic 250 V (3 A) for NO relay output circuit
configurable relay logic 250 V (3 A) for NC relay output circuit
configurable relay logic 30 V DC (3 A) for NO relay output circuit
configurable relay logic 30 V DC (3 A) for NC relay output circuit
open collector 9...30 V (50 mA)

Output frequency 50 kHz for pulse output at DO1

Display type 5 digits 7 segments for 39 parameters

Device application Speed control

Type of installation Indoor/outdoor

Control type Manual using keypad
Using control terminal
Using serial port

Device mounting Wall mounted
DIN rail

Speed accuracy +/- 0.5 % of nominal speed

Protection type Overcurrent
Overvoltage
Undervoltage
Overheating
Overload
Short-circuit
Phase loss
Low light protection

Width 145 mm

Height 230 mm

Depth 177.4 mm

Environment

Relative humidity 0...95 % without condensation

Ambient air temperature for storage -20...65 °C

Quality labels CE

Operating altitude

IP degree of protection IP20

Vibration resistance 5.9 m/s²

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Contractual warranty

Warranty 24 months
